

Ranch Dog 's Load Notes
Property of Ranch Dog Outdoors

Powder	Max Grains	Case Density (%)	Velocity FPS	Pmax (k)
IMR 3031	44.1	96	2445	40.2
Ramshot BigGame	50.2	98	2432	40.2
SNPE Vectan SP 11	50.2	98	2431	40.2
Winchester 748	46.7	88	2427	40.2
IMR 4895	46.7	94	2425	40.2
Alliant Reloder-17	49.9	96	2416	40.2
Norma 203B	47.3	96	2416	40.2
Bofors RP11	47.0	95	2411	40.2
Alliant Reloder-15	47.0	95	2411	40.2
Raufoss RA11	47.0	95	2411	40.2
Hodgdon H4895	45.0	91	2398	40.2
Vihtavuori N135	45.5	101	2394	40.2
Vihtavuori N540	47.2	95	2394	40.2
Norma 202	44.8	92	2391	40.2
Somchem S321	46.4	87	2390	40.2
ADI AR 2206H	45.1	91	2389	40.2
PB Clermont PCL 507	45.7	89	2387	40.2
SNPE Vectan SP 9	47.0	92	2387	40.2
Lovex S062	46.1	96	2387	40.2
Ramshot TAC	45.6	86	2387	40.2
IMR 4320	46.9	96	2386	40.2
Hodgdon H322	41.9	87	2385	40.2
Vihtavuori N150	49.0	105	2383	40.1
PB Clermont PCL 516	48.8	93	2381	40.2
Somchem S341	48.4	91	2379	40.2
Vihtavuori N530	43.5	88	2378	40.2
Vihtavuori N140	45.6	94	2373	40.2
Hodgdon VARGET	46.1	96	2365	40.2
ADI AR 2208	46.1	96	2365	40.2
IMR 4064	45.4	97	2362	40.2
Alliant Reloder-12	43.9	87	2358	40.2
Accurate 2015	41.4	87	2350	40.2
Bofors RP3 NT	48.8	99	2347	40.2
Bofors RP2 NT	44.2	90	2337	40.2
Bofors RP7 NT	48.2	97	2336	40.2
Somchem S335	44.1	91	2330	40.2
Hodgdon Benchmark	42.5	87	2326	40.2
Vihtavuori N133	41.8	92	2323	40.2
Lovex S060	43.2	90	2319	40.2
ADI AR 2206	43.6	89	2312	40.2
Vihtavuori N130	40.0	87	2309	40.2

Notes for Ranch Dog's use only! Any other use is at your own risk!	
Original: 02/22/10	
TLC339-200-RF	
32 Win Spl	
Marlin 338MX	
22"	
OAL = 2.475" MIN	
Load Selection	
Alloy:	
Lyman #2 clone	
Water Quenched	
Case Density	
Max: 105%	
Min: 86%	
Pressure	
Read Pressure_Notes.PDF!	
46.0K Pmax	
40.3K NMP	
Velocity	
Maximum to Max -10%	
No other loads considered!	

